Hand-Wind Grounding Reels

ML2930 Series

Heavy-Duty Hand-Wind



These ruggedly constructed reels are an economical alternative to automatic retracting reels. In addition to lower initial cost, there are fewer parts to maintain, allowing for years of trouble-free service. ML2930 series hand-wind reels also offer highly compact storage of a wide range of cable lengths up to 150'.

Standard Clamp:	100 amp solid copper alligator clip (LE-21C)	
Electrical Resistance:	5 ohms maximum between clamp and mounting base	
Finish:	Yellow enamel	
Capacity:	125' with 5/32" O.D. cable, 150' with 1/8" O.D. cable	

Part Number	Cable Length	Cable Size	Cable Type	Weight
ML2930-MC50	50'	3/32" ID coated to 1/8" OD	Clear PVC coated plated steel	9.5 lbs
ML2930-MY50	50'	3/32" I.D. coated to 5/32" OD	Yellow Hytrel® coated plated steel	9.8 lbs
ML2930-MC75	75'	3/32" ID coated to 1/8" OD	Clear PVC coated plated steel	10.0 lbs
ML2930-MY75	75'	3/32" ID coated to 5/32" OD	Yellow Hytrel coated plated steel	10.3 lbs
ML2930-MC100	100'	3/32" ID coated to 1/8" OD	Clear PVC coated plated steel	10.5 lbs
ML2930-MY100	100	3/32" ID coated to 5/32" OD	Yellow Hytrel coated plated steel	10.8 lbs
ML2930-MC125	125'	3/32" ID coated to 1/8" OD	Clear PVC coated plated steel	11.0 lbs
ML2930-MY125	125'	3/32" ID coated to 5/32" OD	Yellow Hytrel coated plated steel	11.3 lbs
ML2930-MC150	150'	3/32" ID coated to 1/8" OD	Clear PVC coated plated steel	11.5 lbs

Substitute the LE21C Alligator Clip for our heavier duty REB Clamp when using this reel in outdoor areas or with painted, dirty or rusty surfaces. Add "REB" to the end of the part number.

Need a different clamp? Need a specialized wye? We can do customized static ground reels.