

LED EXPLOSION-PROOF STRINGLIGHTS

KEY FEATURES

- cQPSus listed for Class I, Division 1, Groups C & D hazardous locations (conforms to CSA and UL standards).
- Built using Lind Equipment's XP162LED heavy-duty incandescent explosion-proof work lights.
- Ready to use - 9W LED bulbs are pre-installed and factory tested before each shipment.
- Heavy duty construction: Tuffite phenolic handle, aluminum guard, tempered glass globe.
- Heavy-duty 12/3 SOOW cable
- Hanging hooks built from 3/32" PVC-coated steel mounted to T-drops hold lights securely overhead.

Lind Equipment's Explosion-Proof Stringlights are designed and approved to be used in hazardous locations by incorporating LED explosion-proof hand lamps into sturdy t-drops and cable. Our new LED version is 25% brighter than the incandescent version.



PLUG & RECEPTACLE OPTIONS:

- Appleton 15A, 120V explosion-proof plug and receptacle.
- Bare ends.
- Regular, non-hazardous location plug with 25' lead (to be plugged in outside of hazardous location).

SPECIFICATIONS

CORD	12/3 SOOW
BULB	9W replaceable LED bulb.
APPROVALS	cQPSus listed for Class I, Division 1, Groups C & D hazardous locations (conforms to CSA and UL standards).

Part Number	Length	# of Sockets (spaced every 10')	Plug	Receptacle	Lead	Tail
TLS-100XPLED	100'	10	Class 1, Div 1 XP plug	Class 1, Div 1 XP connector	9'	1'
TLS-100XPLEDBL	100'	10	Bare end (no plug)	Bare end (no connector)	9'	1'
TLS-100XPLEDRE	115'	10	Regular (non-haz loc) plug	Blunt end (cannot daisy chain)	25'	n/a
TLS-50XPLED	50'	5	Class 1, Div 1 XP plug	Class 1, Div 1 XP connector	9'	1'
TLS-50XPLEDBL	50'	5	Bare end (no plug)	Bare end (no connector)	9'	1'
TLS-50XPLEDRE	65'	5	Regular (non-haz loc) plug	Blunt end (cannot daisy chain)	25'	n/a
XP162-P1	Replacement LED bulb.					

Our design and engineering team excels at providing customized products for unique applications. We can provide explosion-proof stringlights with alternate lengths, plugs, connectors or number of sockets to meet the specific needs of your application.

