BEACON360 GO DATASHEET

Features

- Cordless & rechargeable.
- As bright as a 500W quartz halogen.
- Low energy usage.
- No bulb replacement required.
- Instant start-up, at full output, even in cold temperatures.
- Cool to the touch.
- Can operate while charging.
- 120V AC charger included.
  **Other AC charger voltages are available at request.*
- IP65 weather and wet location rated.
- 90V-277V input range.
- Approved to UL & CSA standards.
  **Meeting OSHA, MOL/WorkSafe, NEC, and CEC regulations.*

Applications

- Construction.
- Mining.
- Utilities.
- Fabrication workshops.
- First responders & emergency services



LE360LEDC-TR



LE360LEDC-CLAMP



LE360LEDC-MAG



LE360LEDC-FS



OVERVIEW	
Part Number	LE360LEDC
Description	45W Battery Operated LED Area Light
Lumens	• 6,000 lumens at 100% • 3,000 lumens at 50% • 900 lumens at 15%
Charge Time	5 hours
Run Time (Full Charge)	• 4 hours at 100% • 8 hours at 50% • 25 hours at 15%
Weight	9lbs
Construction	Cast aluminum housing with polycarbonate lens
Dimensions	6.5”L X 6.5”W X 12”H
Mounting Options	Bracket (included), 4-8ft Tripod (-TR), Floorstand (-FS), Magnet (-MAG), Scaffold Clamp (-CLAMP)