LIND EQUIPMENT
WORK CONFIDENTLY.

DATA SHEET
40, 50, 60 AMP ELCIs

HIGH POWERED ELCIs

KEY BENEFITS

- *Protect and safeguard equipment, personnel and electrical circuits from the dangerous risks of ground fault leakage.*
- *Comply with electrical codes.*

The Lind High Powered ELCIs are designed for the toughest environments where ground fault protection is needed for high powered equipment. Available in varying trip levels, voltage and amperage, these units will protect equipment and users. The enclosures are industrially designed with impact resistant materials that withstand chemical and U.V. light exposure. In addition, the electrical contacts of this device are electro-magnetically latched so it will not delatch under rough use. Dual LED indication lights display power and fault status.

KEY FEATURES

- *Withstands chemical and U.V. light exposure.*
- *NEMA 4X and 6P wet location rated.*
- *Double insulated and recessed user interface for added safety.*
- *Industrial design for indoor/ outdoor applications.*
- *Dual indication lights displaying power and fault status.*

C SA US



SPECIFICATIONS	
FREQUENCY	60Hz
RESPONSE TIME	25mS max @ 500 Ohm Fault
OPERATING TEMPERATURE	-35°C to 66°C
RESET TYPE	Field selectable - automatic or manual reset
ENCLOSURE	NEMA 4X wet location rated
SWITCHING INTERFACE	Double insulated and recessed

PART NUMBER	VOLTAGE	AMPERAGE	CORD	PHASE	ADJUSTABLE TRIP LEVELS
LECI-601201	120V	60A	6' of 6/3 SOOW cable	1 Ø	6/10/30mA
LECI-402401	240V	40A	6' of 8/3 SOOW cable	1 Ø	6/10/30mA
LECI-402083	208V	40A	2' of 10/4 SOOW cable	3 Ø	6/10/30mA
LECI-402403	240V	40A	2' of 10/4 SOOW cable	3 Ø	6/10/30mA
LECI-602083	208V	60A	6' of 6/4 SOOW cable	3 Ø	6/10/30mA
LECI-602403	240V	60A	6' of 6/4 SOOW cable	3 Ø	6/10/30mA
LECI-404803	480V	40A	6' of 6/4 SOOW cable	3 Ø	6/10/30mA
LECI-604803	480V	60A	6' of 6/4 SOOW cable	3 Ø	6/10/30mA
LECI-606003	600V	60A	2' of 6/4 SOOW cable	3 Ø	6/10/30mA