LIND EQUIPMENT
WORK CONFIDENTLY.

GFCI In-Line Cord Sets

Excellent for industrial plant maintenance, equipment service and construction site applications. Provides compliance with National Electric Codes (NEC) Article 527.6 "Temporary Wiring". Applications include:

- High Pressure Sprayer Washers
- Drain Snakes
- Construction Sites
- Construction Site Power Tools
- Pumps
- Industrial Appliances

Rainproof rated, UL listed for outdoor use. Standard Lengths: 2', 6', 25', 50' Custom cable gauges, lengths and terminations available by special order. To prevent unmonitored equipment startup, manual reset is required after GFCI trip and power outage.

FEATURES

Model 25080L

- Volts /Amps: 120V/20A
- Cord Gauge: 12/3 AWG.
- NEMA 5 - 20 P & R
- Trip Level: 4 - 6 mA

Model 25090L

- Volts /Amps: 240V/15A
- Cord Gauge: 14/3 AWG.
- NEMA 6 - 15 P & R
- Trip Level: 4 - 6 mA

Model 26020L

- Volts /Amps: 120V/15A
- Cord Gauge: 14/3 or 12/3 AWG.
- NEMA 5 - 15 P & R
- Trip Level: 4 - 6 mA

Model 26000L

- Volts /Amps: 240V/20A
- Cord Gauge: 12/3 AWG.
- NEMA 6 - 20 P & R
- Trip Level: 4 - 6 mA

TECHNICAL DATA

Grounded neutral	4 Ohms typical
Trip response time for ground fault and grounded neutral trip	less than 25mS
Voltage surge withstand (MOV Protection)	3kv ringwave test and 4kv/2kA surge immunity test
Radio frequency noise susceptibility	operates within normal limits with 0.5 volts injected on power line 150-230 mHz
Frequency	50 / 60 Hz
Endurance	3,000 operations minimum
Overload Current	six times rated current
Operating temperature range	-35˚C to 66˚C
Effect of 10 Amp turn DC Shock on ground fault trip	5% maximum trip level variation
Insulation voltage	1500 VRMS - 1 Min.
Power On indication	lighted indicator



